

***Super Wear™ Steel Brad Point Spur Machine Drills (No. X200)***

Widely used for cross-grained boring; provides smooth accurate holes.

Product No.	Diameter	T'wist Length	Overall Length	Shank
FC-62164	3/16"	3"	5"	1/2"
FC-62165	1/4"	3"	5"	1/2"
FC-62166	9/32"	3"	5"	1/2"
FC-62167	5/16"	3"	5"	1/2"
FC-62168	11/32"	3"	5"	1/2"
FC-62169	3/8"	3"	5"	1/2"
FC-62170	7/16"	3"	5"	1/2"
FC-62171	1/2"	3"	5"	1/2"
FC-62172	1/4"	4"	6"	1/2"
FC-62173	9/32"	4"	6"	1/2"
FC-62174	5/16"	4"	6"	1/2"
FC-62175	11/32"	4"	6"	1/2"
FC-62176	3/8"	4"	6"	1/2"
FC-62177	13/32"	4"	6"	1/2"
FC-62178	7/16"	4"	6"	1/2"
FC-62179	1/2"	4"	6"	1/2"
FC-62180	17/32"	4"	6"	1/2"
FC-62181	9/16"	4"	6"	1/2"
FC-62182	5/8"	4"	6"	1/2"
FC-62183	11/16"	4"	6"	1/2"
FC-62184	3/4"	4"	6"	1/2"
FC-62185	13/16"	4"	6"	1/2"
FC-62186	7/8"	4"	6"	1/2"
FC-62187	5/16"	4"	6"	1/2"
FC-62188	1"	4"	6"	1/2"



***Carbide-Tipped Brad Point Spur Machine Drills (No.200CT)***

Carbide tipped for drilling plastics, laminates, chip core & tough-to-drill materials.

Product No.	Diameter	Twist Length	Overall Length	Shank
FC-62189	1/4"	3"	5"	1/2"
FC-62190	5/16"	3"	5"	1/2"
FC-62191	3/8"	3"	5"	1/2"
FC-62192	7/16"	3"	5"	1/2"
FC-62193	1/2"	3"	5"	1/2"
FC-62194	5/8"	3"	5"	1/2"
FC-62195	3/4"	3"	6"	1/2"
FC-62196	1/4"	3"	5"	1/2"
FC-62197	5/16"	4"	6"	1/2"
FC-62198	3/8"	4"	6"	1/2"
FC-62199	7/16"	4"	6"	1/2"
FC-62200	1/2"	4"	6"	1/2"
FC-62201	5/8"	4"	6"	1/2"
FC-62202	3/4"	4"	6"	1/2"

