

Carbide-Tipped Drills (No.811CT)

Bores clean, accurate holes in plastic laminates and wood. Spur outlines hole before the chip lifters plane material. Helps prevent cracked edges. Includes solid carbide point.

Product Number	Diameter	Shank Diameter	Nominal Overall Length
FC-62797	1"	1/2"	6"
FC-62798	1-1/8"	1/2"	6"
FC-62799	1-1/4"	1/2"	6"
FC-62800	1-3/8"	1/2"	6"
FC-62801	1-1/2"	1/2"	6"
FC-62802	1-5/8"	1/2"	6"
FC-62803	1-3/4"	1/2"	6"
FC-62804	1-7/8"	1/2"	6"
FC-62805	2"	1/2"	6"
FC-62806	2-1/8"	1/2"	6"
FC-62807	2-1/4"	1/2"	6"
FC-62808	2-1/2"	1/2"	6"
FC-62809	2-3/4"	1/2"	6"
FC-62810	3"	1/2"	6"



Carbide-Tipped 3-Wing Drills (No.812CT)

Designed to bore plastic Formica™ and tempered Masonite™ as well as abrasive materials and hard woods.

Product Number	Diameter	Shank Diameter	Nominal Overall Length
FC-62825**	1/2"	1/2"	6"
FC-62826**	9/16"	1/2"	6"
FC-62827**	5/8"	1/2"	6"
FC-62828	11/16"	1/2"	6"
FC-62829	3/4"	1/2"	6"
FC-62830	13/16"	1/2"	6"
FC-62831	7/8"	1/2"	6"
FC-62832	1"	1/2"	6"
FC-62833	1-1/8"	1/2"	6"
FC-62834	1-1/4"	1/2"	6"
FC-62835	1-3/8"	1/2"	6"
FC-62836	1-1/2"	1/2"	6"
FC-62837	1-5/8"	1/2"	6"
FC-62838	1-3/4"	1/2"	6"
FC-62839	1-7/8"	1/2"	6"
FC-62840	2"	1/2"	6"
FC-62841	2-1/8"	1/2"	6"
FC-62842	2-1/4"	1/2"	6"
FC-62843	2-1/2"	1/2"	6"

Only 2-1/4" through 3" diameter drills are furnished with 2-1/4" long reinforced shaft.

NOTE: **Reduced shank behind wings.