

## Wadkin TS Cutterhead Range - HYDRO With Four or Six Knives

The TS Range delivers cost effective state-of-the-art reliable Hydro-Loc engineering. Simply put, TS Heads hold better and perform better on any moulder, regardless of make or model.

### FOUR KNIVES - Bore Size: 1-13/16"

Knives	Width Inches	Width mm	20° Cut Angle Part #	12° Cut Angle Part #
4	2.5"	60	TS406-46-15U	TS406-46-15M
4	3"	80	TS408-46-15U	TS408-46-15M
4	4"	100	TS410-46-15U	TS410-46-15M
4	5"	130	TS413-46-15U	TS413-46-15M
4	6"	150	TS415-46-15U	TS415-46-15M
4	7"	180	TS418-46-15U	TS418-46-15M
4	9"	230	TS423-46-15U	TS423-46-15M
4	9.5"	240	TS424-46-15U	TS424-46-15M

### FOUR KNIVES - Bore Size: 2-1/8"

Knives	Width Inches	Width mm	20° Cut Angle Part #	12° Cut Angle Part #
4	2.5"	60	TS406-54-15U	TS406-54-15M
4	3"	80	TS408-54-15U	TS408-54-15M
4	4"	100	TS410-54-15U	TS410-54-15M
4	5"	130	TS413-54-15U	TS413-54-15M
4	6"	150	TS415-54-15U	TS415-54-15M
4	7"	180	TS418-54-15U	TS418-54-15M
4	9"	230	TS423-54-15U	TS423-54-15M
4	9.5"	240	TS424-54-15U	TS424-54-15M

### SIX KNIVES - Bore Size: 1-13/16"

Knives	Width Inches	Width mm	20° Cut Angle Part #	12° Cut Angle Part #
6	2.5"	60	TS606-46-15U	TS606-46-15M
6	3"	80	TS608-46-15U	TS608-46-15M
6	4"	100	TS610-46-15U	TS610-46-15M
6	5"	130	TS613-46-15U	TS613-46-15M
6	6"	150	TS615-46-15U	TS615-46-15M
6	7"	180	TS618-46-15U	TS618-46-15M
6	9"	230	TS623-46-15U	TS623-46-15M
6	9.5"	240	TS624-46-15U	TS624-46-15M



TS heads are available with 4, 6, 8, 10, and 12 knives for any spindle diameter.

### Safety Locking Collars



Part #	Full Cap. Threaded
MMT2556	40mm R/H
MMT2558	40mm L/H
MMT2568	1-13/16" R/H
MMT2570	1-13/16" L/H
Part #	Partial Cap. Plain
MMT2590	1-1/2"
MMT2560	40mm
MMT2578	1-13/16"
MMT2586	2-1/8"

We *strongly recommend* the use of Locking Collars with Hydro-Loc Heads as extra insurance to help prevent the head spinning on the shaft.

Continued on next page.